



Product Service

CERTIFICATE

No. Z1A 059966 0298 Rev. 04

Holder of Certificate: Ningbo Boyang Lighting Co., Ltd.

XinZe Village Guanhaiwei Town
315314 Cixi, Zhejiang
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: Cable reels

Tested according to: EN 61242:1997/A13:2017
AfPS GS 2019:01 PAK
EK1 702-20 Rev. 1

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 874102304206-00

Valid until: 2028-10-16

Date, 2023-10-17

(Jie Zhu)

CERTIFICATE

No. Z1A 059966 0298 Rev. 04

Model(s):

OXF-17B-1.5, OXF-17B-2.5,
OXF-25B-1.5, OXF-25B-2.5,
OXF-26B-1.5, OXF-26B-2.5,
OXF-G03M-1.5, OXF-G03M-2.5,
OXF-G15M-1.5, OXF-G15M-2.5,
OXF-G25M-1.5, OXF-G25M-2.5,
OXF-17BU-1.5, OXF-17BU-2.5,
OXF-25BU-1.5, OXF-25BU-2.5,
OXF-26BU-1.5, OXF-26BU-2.5,
OXF-G03MU-1.5, OXF-G03MU-2.5,
OXF-G15MU-1.5, OXF-G15MU-2.5,
OXF-G25MU-1.5, OXF-G25MU-2.5,
OXF-17BU2-1.5, OXF-26BU2-1.5,
OXF-G03MU2-1.5, OXF-G15MU2-1.5,
OXF-G25MU2-1.5, OXF-25BU2-1.5,
OXF-17BU2-2.5, OXF-26BU2-2.5,
OXF-G03MU2-2.5, OXF-G15MU2-2.5,
OXF-G25MU2-2.5, OXF-25BU2-2.5,
OXF-17BU2K-1.5, OXF-26BU2K-1.5,
OXF-G03MU2K-1.5, OXF-G15MU2K-1.5,
OXF-G25MU2K-1.5, OXF-25BU2K-1.5,
OXF-17BU2K-2.5, OXF-26BU2K-2.5,
OXF-G03MU2K-2.5, OXF-G15MU2K-2.5,
OXF-G25MU2K-2.5, OXF-25BU2K-2.5,
OXF-37B-1.5, OXF-37BU-1.5,
OXF-37BU2-1.5, OXF-37BU2K-1.5,
OXF-37B-2.5, OXF-37BU-2.5,
OXF-37BU2-2.5, OXF-37BU2K-2.5.

CERTIFICATE

No. Z1A 059966 0298 Rev. 04

Parameters:

Rated voltage:	230V~
Rated frequency:	50Hz
Rated power:	3200W (cable fully extended) 1100W (cable fully reeled)
Protection class:	I
Degree of protection:	IP20
Type of cable:	H05VV-F 3G1.5mm ² or H05VV-F 3G2.5mm ²
Remark:	For OXP-17BU-1.5, OXP-17BU-2.5, OXP-25BU-1.5, OXP-25BU-2.5, OXP-26BU-1.5, OXP-26BU-2.5, OXP-G03MU-1.5, OXP-G03MU-2.5, OXP-G15MU-1.5, OXP-G15MU-2.5, OXP-G25MU-1.5, OXP-G25MU-2.5, OXP-37BU-1.5, OXP-37BU-2.5: USB rated output voltage:5.0VDC USB rated output current: Single Type A: 2.4A max Type A + Type A: 2.4A max For OXP-17BU2-1.5, OXP-26BU2-1.5, OXP-G03MU2-1.5, OXP-G15MU2-1.5, OXP-G25MU2-1.5, OXP-25BU2-1.5, OXP-17BU2-2.5, OXP-26BU2-2.5, OXP-G03MU2-2.5, OXP-G15MU2-2.5, OXP-G25MU2-2.5, OXP-25BU2-2.5, OXP-17BU2K-1.5, OXP-26BU2K-1.5, OXP-G03MU2K-1.5, OXP-G15MU2K-1.5, OXP-G25MU2K-1.5, OXP-25BU2K-1.5, OXP-17BU2K-2.5, OXP-26BU2K-2.5, OXP-G03MU2K-2.5, OXP-G15MU2K-2.5, OXP-G25MU2K-2.5, OXP-25BU2K-2.5, OXP-37BU2-1.5, OXP-37BU2K-1.5, OXP-37BU2-2.5, OXP-37BU2K-2.5: USB rated output voltage:5.0VDC USB rated output current: Single Type A: 3.0A max Single Type C: 3.0A max Type A + Type C: 3.0A max USB rated output voltage:9.0VDC USB rated output current: Single Type A: 2.0A max Single Type C: 2.2A max USB rated output voltage:12.0VDC USB rated output current: Single Type A:1.5A max Single Type C: 1.67A max

CERTIFICATE

No. Z1A 059966 0298 Rev. 04

Model	Rated Power Fully reeled/ Extended	Type of cable	Cable length	With two USB ports, Type A +Type A	With two USB ports, Type A +Type C	With switch
EXP-17B-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.10m	No	No	No
EXP-26B-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.5m	No	No	No
EXP-G03M-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.3m	No	No	No
EXP-G15M-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	No	No	No
EXP-G25M-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.25m	No	No	No
EXP-25B-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	No	No	No
EXP-17B-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.8m	No	No	No
EXP-26B-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.4m	No	No	No
EXP-G03M-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.2m	No	No	No
EXP-G15M-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.12m	No	No	No
EXP-G25M-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.20m	No	No	No
EXP-25B-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.12m	No	No	No
EXP-17BU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.10m	Yes	No	No
EXP-17BU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.10m	Yes	No	No
EXP-26BU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.5m	Yes	No	No
EXP-26BU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.5m	Yes	No	No
EXP-G03MU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.3m	Yes	No	No
EXP-G03MU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.3m	Yes	No	No
EXP-G15MU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	Yes	No	No

CERTIFICATE

No. Z1A 059966 0298 Rev. 04

Model	Rated Power Fully reeled/ Extended	Type of cable	Cable length	With two USB ports, Type A +Type A	With two USB ports, Type A +Type C	With switch
EXP-G15MU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	Yes	No	No
EXP-G25MU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.25m	Yes	No	No
EXP-G25MU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.25m	Yes	No	No
EXP-25BU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	Yes	No	No
EXP-25BU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	Yes	No	No
EXP-17BU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.10m	No	Yes	No
EXP-26BU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.5m	No	Yes	No
EXP-G03MU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.3m	No	Yes	No
EXP-G15MU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	No	Yes	No
EXP-G25MU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.25m	No	Yes	No
EXP-25BU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	No	Yes	No
EXP-17BU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.10m	No	Yes	No
EXP-26BU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.5m	No	Yes	No
EXP-G03MU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.3m	No	Yes	No
EXP-G15MU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	Yes	No
EXP-G25MU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.25m	No	Yes	No
EXP-25BU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	Yes	No
EXP-17BU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.10m	No	Yes	Yes
EXP-26BU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.5m	No	Yes	Yes
EXP-G03MU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.3m	No	Yes	Yes

CERTIFICATE

No. Z1A 059966 0298 Rev. 04

Model	Rated Power Fully reeled/ Extended	Type of cable	Cable length	With two USB ports, Type A +Type A	With two USB ports, Type A +Type C	With switch
EXP-G15MU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	No	Yes	Yes
EXP-G25MU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.25m	No	Yes	Yes
EXP-25BU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.15m	No	Yes	Yes
EXP-17BU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.10m	No	Yes	Yes
EXP-26BU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.5m	No	Yes	Yes
EXP-G03MU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.3m	No	Yes	Yes
EXP-G15MU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	Yes	Yes
EXP-G25MU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.25m	No	Yes	Yes
EXP-25BU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	Yes	Yes
EXP-37B-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.20m	No	No	No
EXP-37BU-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.20m	Yes	No	No
EXP-37BU2-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.20m	No	Yes	No
EXP-37BU2K-1.5	1100W/3200W	H05VV-F 3G1.5mm ²	Max.20m	No	Yes	Yes
EXP-37B-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	No	No
EXP-37BU-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	Yes	No	No
EXP-37BU2-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	Yes	No
EXP-37BU2K-2.5	1100W/3200W	H05VV-F 3G2.5mm ²	Max.15m	No	Yes	Yes